

## TECHNICAL DATA SHEET

**ARTICLE CODE: SRL 11**

### LANYARDS



Shock absorbing Double polyamide rope lanyard with scaffold hook and karabiner. Allows to stay connected and protected during move from one location to another. During a fall the Shock absorbing lanyards arrest the generated forces.

#### Key Benefits:

1. Reduce the risk of injuries.
2. Protection from Falls.
3. Restrict free and unsecured movement at height.
4. Energy Absorber.

#### Construction:

- 12 mm dia 3 strand twisted rope.
- One side steel karabiner & other two side Scaffold hook.
- Rope length: 1.8 Mtr.
- Shock Absorber Length : 0.2 meter
- Breaking strength: 23 kN (Min)
- Weight: 2 KG (Approx)



#### STANDARD:

Conforms to EN 355:2002

As per IS 3521 (Part 2):2021 & IS 3521 (Part 5):2021

Care instruction and storage	Store in a cool dry place. Avoid damp areas, chemicals, and sharp objects. Keep away from heat.
Cleaning	Use either mild soap and water or a mild, bleach-free cleaning solution that won't damage the rope.
Inspection	Should be inspected frequently, both before each use and in every 6 months interval. Damaged or defective lanyards should be discarded from service immediately after inspection.