


TECHNICAL DATA SHEET

ARTICLE CODE: SFH 121

FULL BODY HARNESS



General purpose fall arrest harness.
Suitable for construction, tower or ladder job.

Attachment point:

One common dorsal d-ring for fall arrest.

Construction:

Dope dyed high quality polyester webbing.

Webbing Width : 44 +/-1 mm

Webbing color: Yellow and Black

Webbing Breaking Strength : 23 kN

Safe Working Load Capacity : 100 kg

Fall indicator to stop reuse of harness after a major fall.

Dual color scheme for easy differentiation.

Stitching Thread Material : High tenacity polyester.

Thread Color : White

Metal Components : Alloy steel, zinc plated, free from sharp edges.

Adaptability:

Adjustable thigh strap.

Adjustable chest strap.

Ergonomics:

Ideally positioned sit strap for extended comfort.

Weight:

985 Grm. (approx.)



Compliance:

IS: 3521 (Part I) 2021

Conforms to EN 361.

Application	<ul style="list-style-type: none"> ○ Working at height ○ Fall arrest
Care instruction and storage	Store in a cool dry place. Avoid damp areas, chemicals, and sharp objects. Keep away from heat.
Cleaning	Use either mild soap and water or a mild, bleach-free cleaning solution that won't damage the webbing.
Inspection	Full-body harnesses should be inspected frequently, both before each use and in every 6 months interval. Damaged or defective harnesses should be discarded from service immediately after inspection.