

TECHNICAL DATA SHEET

ARTICLE CODE: SFH 144

FULL BODY HARNESS

Full Body harness with work positioning waist pad.

Attachment point:

One common dorsal d-ring for fall arrest.

Two front D-ring at chest point.

Two lateral D-ring at waist level for work positioning job.

Construction:

Dope dyed high quality polyester webbing.

Webbing Width : 44 +/-1 mm

Webbing color: Yellow and Black

Webbing Breaking Strength : 23 kN

Safe Working Load Capacity : 100 kg

Fall indicator to stop reuse of harness after a major fall.

Dual color scheme for easy differentiation.

Stitching Thread Material : High tenacity polyester. Thread

Color : White

Metal Components : Alloy steel, zinc plated, free from sharp edges.

Adaptability:

Adjustable shoulder & thigh strap.

Adjustable chest strap.

Ergonomics:

Ideally positioned sit strap for extended comfort.

Weight:

1.53 KG (approx.)



Compliance:

IS: 3521 (Part I) 2021

Conforms to EN 361.

EN 358.

| | |
|------------------------------|--|
| Application | <ul style="list-style-type: none"> ○ Working at height ○ Fall arrest ○ Work positioning ○ Ladder climbing |
| Care instruction and storage | Store in a cool dry place. Avoid damp areas, chemicals, and sharp objects. Keep away from heat. |
| Cleaning | Use either mild soap and water or a mild, bleach-free cleaning solution that won't damage the webbing. |
| Inspection | Full-body harnesses should be inspected frequently, both before each use and in every 6 months interval. Damaged or defective harnesses should be discarded from service immediately after inspection. |